

OUTA-DOR THERM 1.3

LEAF

| | |
|---------------|---|
| Thickness: | 55mm. |
| Material: | 1.2mm Magnelis® |
| Infill: | Mineralwool. |
| Construction: | Two 1.2mm sheets mechanically fixed together, by bonding two steel skins to the core. |
| Opening: | Inward & outward. |

FRAME

| | |
|-------------------|---|
| Profile: | C frame - single rebate, thermally reducing.* |
| Material: | 1.5mm Magnelis® |
| Infill: | Mineralwool. |
| Hinges: | Arrone AR8186. |
| Frame Extensions: | Supplied as standard to provide additional protection to the fixings against jemmys and to accommodate site tolerances of -0mm/+15mm each side. |

CONFIGURATIONS

| | |
|----------------|---|
| Vision Panels: | Yes. |
| Louvres: | Yes. |
| Side Panels: | Yes - solid or glazed. Solid panels feature a mineralwool infill. |
| Over Panels: | Yes - solid or glazed. Solid panels feature a mineralwool infill. |
| Hardware: | Arrone deadlock. |

* Thermal values may be affected by the addition of apertures; side panels; and/or over panels.
U values have been calculated using a C frame only.

FRAME DIMENSIONS

| Doorset | Max width | Max height |
|---------|-----------|------------|
| Single | 1453mm | 2769mm |
| Double | 2832mm | 2769mm |

CERTIFICATION

| | |
|------------------|--|
| Thermal Value: | 1.3W/(m ² K). |
| Acoustic rating: | Single doorset - 34dB. Double doorset - 36dB. |

WARRANTY

| | |
|-----------|-----------|
| C3 areas: | 10 years. |
| C4 areas: | 5 years. |
| C5 areas: | 3 years. |
| Hardware: | 5 years. |